

What is claimed is:

1. A power supply for an implantable cardioverter-defibrillator for subcutaneous positioning between the third rib and the twelfth rib and using a lead system that does not directly contact a patient's heart or reside in the intrathorasic blood vessels and for providing anti-tachycardia pacing energy to the heart, the power supply comprising:

a capacitor subsystem for storing the anti-tachycardia pacing energy for delivery to the patient's heart; and

a battery subsystem electrically coupled to the capacitor subsystem for providing the anti-tachycardia pacing energy to the capacitor subsystem.

2. The power supply of claim 1, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 5 volts to approximately 500 volts.

3. The power supply of claim 2, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 5 volts to approximately 25 volts.

4. The power supply of claim 2, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 25 volts to approximately 50 volts.

5

5. The power supply of claim 2, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 50 volts to approximately 75 volts.

6. The power supply of claim 2, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 75 volts to approximately 100 volts.

7. The power supply of claim 2, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 100 volts to approximately 150 volts.

20

8. The power supply of claim 2, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 150 volts to approximately 200 volts.

9. The power supply of claim 2, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 200 volts to approximately 250 volts.

10. The power supply of claim 2, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 250 volts to approximately 300 volts.

11. The power supply of claim 2, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 300 volts to approximately 350 volts.

12. The power supply of claim 2, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 350 volts to approximately 400 volts.

13. The power supply of claim 2, wherein the anti-tachycardia pacing energy comprises a biphasic waveform

having a peak voltage that is approximately 400 volts to approximately 450 volts.

5 14. The power supply of claim 2, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 450 volts to approximately 500 volts.

10 15. The power supply of claim 1, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a pulse width that is approximately 2 milliseconds to approximately 40 milliseconds.

15 16. The power supply of claim 15, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a pulse width that is approximately 2 milliseconds to approximately 10 milliseconds.

20 17. The power supply of claim 15, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a pulse width that is approximately 10 milliseconds to approximately 20 milliseconds.

18. The power supply of claim 15, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a pulse width that is approximately 20 milliseconds to approximately 30 milliseconds.

5

19. The power supply of claim 15, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a pulse width that is approximately 30 milliseconds to approximately 40 milliseconds.

20. The power supply of claim 1, wherein the anti-tachycardia pacing energy comprises a biphasic waveform further comprising a positive voltage portion and a negative voltage portion.

21. The power supply of claim 20, wherein the positive voltage portion further comprises a tilt of approximately 10% to approximately 90%.

22. The power supply of claim 21, wherein the tilt is approximately 50%.

23. The power supply of claim 20, wherein the negative voltage portion further comprises a tilt of approximately 10% to approximately 90%.

5 24. The power supply of claim 23, wherein the tilt is approximately 50%.

10 25. The power supply of claim 1, wherein the anti-tachycardia pacing energy comprises a biphasic waveform that is provided at a rate of approximately 100 to approximately 300 stimuli/minute.

15 26. The power supply of claim 25, wherein the biphasic waveform is provided after a patient's heart rate is greater than or equal to approximately 100 beats/minute.

20 27. The power supply of claim 26, wherein the biphasic waveform is provided after a patient's heart rate is associated with a monomorphic ECG pattern.

28. The power supply of claim 1, wherein the lead system comprises an electrode located proximate the sternum and anterior portion of the patient's heart.

29. The power supply of claim 1, wherein the anti-tachycardia pacing energy comprises burst pacing energy.

30. The power supply of claim 1, wherein the anti-tachycardia pacing energy comprises ramp pacing energy.

31. A voltage output system for an implantable cardioverter-defibrillator for subcutaneous positioning between the third rib and the twelfth rib and using a lead system that does not directly contact a patient's heart or reside in the intrathorasic blood vessels and for providing anti-tachycardia pacing energy to the heart, the power supply comprising:

an energy storage system for storing the anti-tachycardia pacing energy for delivery to the patient's heart; and

an energy source system electrically coupled to the capacitor subsystem for providing the anti-tachycardia pacing energy to the capacitor subsystem.

32. The voltage output system of claim 31, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 5 volts to approximately 500 volts.

33. The voltage output system of claim 32, wherein
the anti-tachycardia pacing energy comprises a biphasic
waveform having a peak voltage that is approximately 5
volts to approximately 25 volts.

34. The voltage output system of claim 32, wherein
the anti-tachycardia pacing energy comprises a biphasic
waveform having a peak voltage that is approximately 25
volts to approximately 50 volts.

35. The voltage output system of claim 32, wherein
the anti-tachycardia pacing energy comprises a biphasic
waveform having a peak voltage that is approximately 50
volts to approximately 75 volts.

36. The voltage output system of claim 32, wherein
the anti-tachycardia pacing energy comprises a biphasic
waveform having a peak voltage that is approximately 75
volts to approximately 100 volts.

37. The voltage output system of claim 32, wherein
the anti-tachycardia pacing energy comprises a biphasic

waveform having a peak voltage that is approximately 100 volts to approximately 150 volts.

38. The voltage output system of claim 32, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 150 volts to approximately 200 volts.

39. The voltage output system of claim 32, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 200 volts to approximately 250 volts.

40. The voltage output system of claim 32, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 250 volts to approximately 300 volts.

41. The voltage output system of claim 32, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 300 volts to approximately 350 volts.

42. The voltage output system of claim 32, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 350 volts to approximately 400 volts.

5

43. The voltage output system of claim 32, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 400 volts to approximately 450 volts.

44. The voltage output system of claim 32, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 450 volts to approximately 500 volts.

45. The voltage output system of claim 31, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a pulse width that is approximately 2 milliseconds to approximately 40 milliseconds.

20

46. The voltage output system of claim 45, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a pulse width that is approximately 2 milliseconds to approximately 10 milliseconds.

47. The voltage output system of claim 45, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a pulse width that is approximately 10 milliseconds to approximately 20 milliseconds.

48. The voltage output system of claim 45, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a pulse width that is approximately 20 milliseconds to approximately 30 milliseconds.

49. The voltage output system of claim 45, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a pulse width that is approximately 30 milliseconds to approximately 40 milliseconds.

50. The voltage output system of claim 31, wherein the anti-tachycardia pacing energy comprises a biphasic waveform further comprising a positive voltage portion and a negative voltage portion.

51. The voltage output system of claim 50, wherein the positive voltage portion further comprises a tilt of approximately 10% to approximately 90%.

52. The voltage output system of claim 51, wherein the tilt is approximately 50%.

5 53. The voltage output system of claim 50, wherein the negative voltage portion further comprises a tilt of approximately 10% to approximately 90%.

54. The voltage output system of claim 53, wherein the tilt is approximately 50%.

55. The voltage output system of claim 31, wherein the anti-tachycardia pacing energy comprises a biphasic waveform that is provided at a rate of approximately 100 to approximately 300 stimuli/minute.

56. The voltage output system of claim 55, wherein the biphasic waveform is provided after a patient's heart rate is greater than or equal to approximately 100
20 beats/minute.

57. The voltage output system of claim 56, wherein the biphasic waveform is provided after a patient's heart rate is associated with a monomorphic ECG pattern.

58. The voltage output system of claim 31, wherein the lead system comprises an electrode located proximate the sternum and anterior portion of the patient's heart.

5

59. The voltage output system of claim 31, wherein the anti-tachycardia pacing energy comprises burst pacing energy.

60. The voltage output system of claim 31, wherein the anti-tachycardia pacing energy comprises ramp pacing energy.

61. An implantable cardioverter-defibrillator for subcutaneous positioning between the third rib and the twelfth rib within a patient, the implantable cardioverter-defibrillator comprising:

a housing having an electrically conductive surface on an outer surface of the housing;

a lead assembly electrically coupled to the housing and having an electrode, wherein the lead assembly does not directly contact the patient's heart or reside in the intrathorasic blood vessels;

20

a capacitor subsystem located within the housing and electrically coupled to the electrically conductive surface and the electrode for storing anti-tachycardia pacing energy and for delivering the anti-tachycardia pacing energy to the patient's heart through the electrically conductive surface and the electrode; and

a battery subsystem electrically coupled to the capacitor subsystem for providing the anti-tachycardia pacing energy to the capacitor subsystem.

62. The implantable cardioverter-defibrillator of claim 61, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 5 volts to approximately 500 volts.

63. The implantable cardioverter-defibrillator of claim 62, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 5 volts to approximately 25 volts.

64. The implantable cardioverter-defibrillator of claim 62, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 25 volts to approximately 50 volts.

65. The implantable cardioverter-defibrillator of
claim 62, wherein the anti-tachycardia pacing energy
comprises a biphasic waveform having a peak voltage that is
approximately 50 volts to approximately 75 volts.

66. The implantable cardioverter-defibrillator of
claim 62, wherein the anti-tachycardia pacing energy
comprises a biphasic waveform having a peak voltage that is
approximately 75 volts to approximately 100 volts.

67. The implantable cardioverter-defibrillator of
claim 62, wherein the anti-tachycardia pacing energy
comprises a biphasic waveform having a peak voltage that is
approximately 100 volts to approximately 150 volts.

68. The implantable cardioverter-defibrillator of
claim 62, wherein the anti-tachycardia pacing energy
comprises a biphasic waveform having a peak voltage that is
approximately 150 volts to approximately 200 volts.

69. The implantable cardioverter-defibrillator of
claim 62, wherein the anti-tachycardia pacing energy

comprises a biphasic waveform having a peak voltage that is approximately 200 volts to approximately 250 volts.

5 70. The implantable cardioverter-defibrillator of claim 62, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 250 volts to approximately 300 volts.

10 71. The implantable cardioverter-defibrillator of claim 62, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 300 volts to approximately 350 volts.

15 72. The implantable cardioverter-defibrillator of claim 62, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 350 volts to approximately 400 volts.

20 73. The implantable cardioverter-defibrillator of claim 62, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 400 volts to approximately 450 volts.

74. The implantable cardioverter-defibrillator of claim 62, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 450 volts to approximately 500 volts.

5

75. The implantable cardioverter-defibrillator of claim 61, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a pulse width that is approximately 2 milliseconds to approximately 40 milliseconds.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000

76. The implantable cardioverter-defibrillator of claim 75, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a pulse width that is approximately 2 milliseconds to approximately 10 milliseconds.

20

77. The implantable cardioverter-defibrillator of claim 76, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a pulse width that is approximately 10 milliseconds to approximately 20 milliseconds.

78. The implantable cardioverter-defibrillator of
claim 76, wherein the anti-tachycardia pacing energy
comprises a biphasic waveform having a pulse width that is
approximately 20 milliseconds to approximately 30
5 milliseconds.

79. The implantable cardioverter-defibrillator of
claim 76, wherein the anti-tachycardia pacing energy
comprises a biphasic waveform having a pulse width that is
approximately 30 milliseconds to approximately 40
10 milliseconds.

80. The implantable cardioverter-defibrillator of
claim 61, wherein the anti-tachycardia pacing energy
comprises a biphasic waveform further comprising a positive
voltage portion and a negative voltage portion.

81. The implantable cardioverter-defibrillator of
claim 80, wherein the positive voltage portion further
20 comprises a tilt that is approximately 10% to approximately
90%.

82. The implantable cardioverter-defibrillator of
claim 81, wherein the tilt is approximately 50%.

83. The implantable cardioverter-defibrillator of claim 80, wherein the negative voltage portion further comprises a tilt of approximately 10% to approximately 90%.

5

84. The implantable cardioverter-defibrillator of claim 83, wherein the tilt is approximately 50%.

85. The implantable cardioverter-defibrillator of claim 61, wherein the anti-tachycardia pacing energy comprises a biphasic waveform that is provided at a rate of approximately 100 to approximately 300 stimuli/minute.

86. The implantable cardioverter-defibrillator of claim 85, wherein the biphasic waveform is provided after a patient's heart rate is greater than or equal to approximately 100 beats/minute.

87. The implantable cardioverter-defibrillator of claim 86, wherein the biphasic waveform is provided after a patient's heart rate is associated with a monomorphic ECG pattern.

20

88. The implantable cardioverter-defibrillator of claim 61, wherein the lead system comprises an electrode located proximate the sternum and anterior portion of the patient's heart.

5

89. The implantable cardioverter-defibrillator of claim 60, wherein the anti-tachycardia pacing energy comprises burst pacing energy.

90. The implantable cardioverter-defibrillator of claim 60, wherein the anti-tachycardia pacing energy comprises ramp pacing energy.

91. A method for supplying power for an implantable cardioverter-defibrillator for subcutaneous positioning between the third rib and the twelfth rib and using a lead system that does not directly contact a patient's heart or reside in the intrathorasic blood vessels and for providing anti-tachycardia pacing energy to the heart, the method comprising:

20

generating anti-tachycardia pacing energy;

storing the anti-tachycardia pacing energy; and

delivering the anti-tachycardia pacing energy to the patient's heart.

92. The method of claim 91, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 5 volts to approximately 500 volts.

93. The method of claim 92, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 5 volts to approximately 25 volts.

94. The method of claim 92, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 25 volts to approximately 50 volts.

95. The method of claim 92, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 50 volts to approximately 75 volts.

96. The method of claim 92, wherein the anti-tachycardia pacing energy comprises a biphasic waveform

having a peak voltage that is approximately 75 volts to
approximately 100 volts.

5 97. The method of claim 92, wherein the anti-
tachycardia pacing energy comprises a biphasic waveform
having a peak voltage that is approximately 100 volts to
approximately 150 volts.

10 98. The method of claim 92, wherein the anti-
tachycardia pacing energy comprises a biphasic waveform
having a peak voltage that is approximately 150 volts to
approximately 200 volts.

15 99. The method of claim 92, wherein the anti-
tachycardia pacing energy comprises a biphasic waveform
having a peak voltage that is approximately 200 volts to
approximately 250 volts.

20 100. The method of claim 92, wherein the anti-
tachycardia pacing energy comprises a biphasic waveform
having a peak voltage that is approximately 250 volts to
approximately 300 volts.

101. The method of claim 92, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 300 volts to approximately 350 volts.

5

102. The method of claim 92, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 350 volts to approximately 400 volts.

103. The method of claim 92, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 400 volts to approximately 450 volts.

104. The method of claim 92, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a peak voltage that is approximately 450 volts to approximately 500 volts.

20

105. The method of claim 91, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a pulse width that is approximately 2 milliseconds to approximately 40 milliseconds.

106. The method of claim 105, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a pulse width that is approximately 2 milliseconds to approximately 10 milliseconds.

107. The method of claim 105, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a pulse width that is approximately 10 milliseconds to approximately 20 milliseconds.

108. The method of claim 105, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a pulse width that is approximately 20 milliseconds to approximately 30 milliseconds.

109. The method of claim 105, wherein the anti-tachycardia pacing energy comprises a biphasic waveform having a pulse width that is approximately 30 milliseconds to approximately 40 milliseconds.

110. The method of claim 91, wherein the anti-tachycardia pacing energy comprises a biphasic waveform

further comprising a positive voltage portion and a
negative voltage portion.

111. The method of claim 110, wherein the positive
voltage portion further comprises a tilt of approximately
10% to approximately 90%.

112. The method of claim 111, wherein the tilt is
approximately 50%.

113. The method of claim 110, wherein the negative
voltage portion further comprises a tilt of approximately
10% to approximately 90%.

114. The method of claim 113, wherein the tilt is
approximately 50%.

115. The method of claim 91, wherein the anti-
tachycardia pacing energy comprises a biphasic waveform
that is provided at a rate of approximately 100 to
approximately 300 stimuli/minute.

116. The method of claim 115, wherein the biphasic waveform is provided after a patient's heart rate is greater than or equal to approximately 100 beats/minute.

5

117. The method of claim 116, wherein the biphasic waveform is provided after a patient's heart rate is associated with a monomorphic ECG pattern.

118. The method of claim 91, wherein the lead system comprises an electrode located proximate the sternum and anterior portion of the patient's heart.

119. The method of claim 91, wherein the anti-tachycardia pacing energy comprises burst pacing energy.

120. The method of claim 91, wherein the anti-tachycardia pacing energy comprises ramp pacing energy.

10
9
8
7
6
5
4
3
2
1